# High Pressure 3-Stage Jet Pump Model 325SCRD



### **MODEL FEATURES**

- Self-contained, portable pump, jet pump unit
- Capable of producing high pressure flow for jetting standard wellpoints, well casings, or pilings
- Operates efficiently under intermittent flow conditions

## **PUMP**

SIZE: 3-stage Horizontal 6" x 5" x

CASING: Class 30 cast iron IMPELLER: Enclosed-type, single suction, bronze

SEAL: Packing in bronze gland or

Type 1 mechanical seal

WEAR RINGS: Bronze on Casing

and Impeller

SHAFT: High tensile steel SHAFT SLEEVE: Bronze or

Stainless Steel

### **ENGINE**

MAKE: John Deere MODEL: 6090

DISPLACEMENT: 549 cu in.
GOVERNOR: Electronic
LUBRICATION:
Constant pressure, full flow
AIR CLEANER: Dry type reusable
ELECTRICAL SYSTEM: 12V DC
SAFETY SHUTDOWNS: High
head temperature, low oil

TYPE: 6-cylinder, 4-cycle liquid-

cooled, turbo-charged diesel

pressure MANUFACTURER'S PERFORMANCE:

Rated Power—hp (kW)

intermittent: 325 (242) Rated speed—rpm: 2000

### STANDARD PRIMING SYSTEM

TYPE: Hand-operated diaphragm primer

### OPTIONAL PRIMING SYSTEM—VACUUM PUMP

MODEL: Wallenstein

TYPE: Rotary vane, air cooled, oil

**lubricated** 

CAPACITY: 30 cubic inch SCFM

@ 850 rpm nominal

CASING: Class 30 cast iron

ROTOR: Class 30 cast iron with self-adjusting, Ferobestos®

vanes

### STANDARD FITTINGS

DISCHARGE: 6" Flange INLET: 6" Flange

### STANDARD EQUIPMENT

- I-beam skid frame
- Center point lifting bail
- Battery box
- Vacuum gauge with liquid filled, stainless steel case

### **AVAILABLE OPTIONS**

 Optional integral fuel tank frame

### PHYSICAL DIMENSIONS


WEIGHT: 7550 lbs. LENGTH: 168" WIDTH: 44" HEIGHT: 78"

In the interest of product improvement, specifications may change without notice.



5306 Clinton Drive, Houston, TX 77020 (713)676-8000 Fax: (713)675-4820 web: www.griffindewatering.com e-mail: rachel.smith@griffinpump.com © Copyright Griffin Dewatering, LLC 2021

## High Pressure 3-Stage Jet Model: 325SCRD



In the interest of product improvement, specifications may change without notice.

